# RAIDON



## InTANK iR2824

### Internal RAID Module for Data Security and Data on the Move

RAID Setting Button, LCD Display and LED Indicators for System Monitoring

iR2824 provides RAID mode setting buttons and built-in LCD & LED display functions that can monitor and display the RAIDbox's status. The iR2824 supports 2 x 5.25" CD-ROM size, it can perfectly match servers, industrial computers, and workstations.

iR2824 can use two 3.5" or 2.5" SATA disk to set
one RAID 1 or RAID 0 group, and provides one
additional 2.5" SATA disk as independence disk
(JBOD) for diversify usage. It is the ideal Hardware
RAID module for Data Security and Data on the
Move.

#### Features

- 1. RAID Mode Setting Buttons
- 2. LCD for System Monitoring
- 3. Supports Hardware RAID 1/0
- 4. Support 2 x 3.5"/2.5" SATA Disk (HDD/SSD)(RAID)
- 5. Support 1 x 2.5" SATA Disk (HDD/SSD)(JBOD)
- 6. Plug & Play, No Driver Needed
- 7. GUI can show the disk S.M.A.R.T. information (Windows only)
- 8. Disk Hot-swappable

### RAIDON

#### **User-friendly Display**

iR2824 provides RAID mode button setting, and is equipped with clear readable LCD display and LED indicators for system monitoring during operation so users can easily grasp the status of the system at all times. Moreover, it comes with visual and audio alarms whenever failure occurs.



#### Easy-to-use Disk Tray Module

RAIDON's easy-to-use disk tray module comes with a key lock and secure the disk with screws. User can buy several disk tray modules and secured the disks first, once there is one disk in iR2824 is failure, just replace the disk directly. It can greatly reduce the wait time for system maintenance. The disk tray provides a key lock, which will not be easily extracted, increasing data security.




#### GUI can Show the Disk S.M.A.R.T Information

iR2824 provides the GUI that can show the S.M.A.R.T (Self Monitoring, Analysis, and the Reporting Technology) Information of disks. Just open the RAIDGuide Manager Utility, user can using it to know the disks' status, and could even to replace any disk which is might be damaged in advance to help an even better protection for all your data.

RAIDON					Speed 6G SA DGuide N		
Device1	RDD1 HDD2 SM4 Goo		DD1 : S	amsung SSI	D 850 PRO 1280 Updates after		nd
System Status	D	Value	Worst	Threshold	RAW	Status	
	05-Reallocated sector count	100	100	10	000000000000	Good	-
Firmware Upgrade	09-Power-on hours count	99	99	0	0000000007B	Good	
	0C-Power cycle count	99	99	0	00000000078	Good	
	B1h-UnKnown	98	98	0	00000000004C	Good	
	B3h-UnKnown	100	100	10	000000000000	Good	
E-Mail Notify	B5h-UnKnown	100	100	10	000000000000	Good	
	B6h-UnKnown	100	100	10	00000000000000000	Good	
	B7-SATA Downshift Error Court	100	100	10	000000000000	Good	
S.M.A.R.T. About	BB-Reported Uncorrectable En	100	100	0	000000000000	Good	
	BE-Airflow Temperature	69	46	0	00000000001F	Good	
	C3-Hardware ECC recovered	200	200	0	000000000000	Good	
	C7-UDMA CRC error rate	100	100	0	000000000000000000000000000000000000000	Good	
	EBh-UnKnown	99	99	0	00000000064	Good	
	F1-Total LBAs Written	99	99	0	000307982920	Good	



### RAIDON



#### **Product Appearance Description**



A. 2.5" HDD status indicator LED B. 2.5" HDD tray

C. LCD Display

D. RAID Setting Button E. Alarm indicator LED G. RAID HDD tray H. Key Lock I. HDD status indicator LED J. RS232 switch K. SATA Port(for 2.5" HD host) L. SATA Port(for RAID host) M. Power Socket N. Cooling Fan

Interfaces	2 x SATA III (6Gbps)(One for RAID and another for JBOD)					
Compatible Drive	2 x 3.5"/2.5" SATA Drive(HDD/SSD)(RAID)					
	1 x 2.5" SATA Drive (HDD/SSD)(JBOD)(Under 9.5mm height)					
Certification	CE / FCC					
RAID Mode	1 x RAID 1 / RAID 0 Group					
	1 x JBOD (Single)					
<b>Operating System Support</b>	perating System Support Windows, Linux					
Cooling Fan	1 x 6cm Fan					
	*Line voltage: 12V+5V, DC					
Electrical and Operating	*Operating temperature: 0° to 40° C (32° to 104° F)					
Requirements	*Storage temperature: -20° to 47° C (-4° to 116° F)					
	*Relative humidity: 5% to 95%, no condensing					
Size	Height: 84 mm Width: 148 mm Depth: 202 mm					
Product Code	EAN:					
Product Code	UPC :					
Carton	8 pcs per carton					
	1 x iR2824					
Package Accessories	1 x SATA Cable					
ruckuge Accessories	1 x Accessory					
	1 x Quick Installation Guide					