

RAIDON



SafeTANK GR3660-TB3

2-Bay 2.5"/3.5" SAS/SATA III HDD/SSD Hardware RAID Storage

2 Thunderbolt™ 3 ports, 1 Mini DisplayPort, Hot-Swappable Drive

A software RAID storage system is unable to overcome the problems associated with cross-platform usage. It is only through hardware RAID controller chipsets that users can use these hard drives concurrently in Mac or Windows computers. With the GR3660's built-in hardware RAID controller chipset and Thunderbolt™ 3 host interface, not only does it promise high transmission speed, it also eliminates the cross-platform usage issues associated with RAID 0 or RAID 1 setups. Also, with hardware RAID, all data is computed and processed by the built-in CPU. With such advantages, your computer performance can be focused on running the software and work, instead of handling the storage device's transmission issues.

Features

1. Hardware RAID that works seamlessly between Macs and PCs.
2. The GR3660-TB3 is equipped with three configuration modes to suit every need.
 - RAID 0/1/JBOD.
3. Thunderbolt™ 3 (USB-C) brings you 40 Gbps extreme high data transfer speed.
4. GR3660-TB3 to support 2 x 3.5" / 2.5" SAS/SATA HDD/SSD.
5. Thunderbolt™ 3 The USB-C that does it all.
 - Support 15W (5V/3A) Power Delivering.
 - Mini DisplayPort connect DVI 、HDMI 、VGA display devices.

RAIDON
www.raidon.com.tw



TEL : +886-2-2278-9697
FAX : +886-2-2278-9659
E-Mail : sales1@raidon.com.tw
7F-9, No.16, Lane. 609, Sec.5, Chung-Hsin Rd.,
San-Chung Dist., New Taipei City, Taiwan (R.O.C.)



A. HDD access Indicator
 B. Removable drive tray
 C. HDD tray key lock
 D. Power socket
 E. Power switch

F. Fan
 G. Mini DisplayPort
 H. Thunderbolt™ port
 I. Port RAID Dip-switch
 J. Reset Button

產品規格

GR3660-TB3	
Interface	Thunderbolt™ 3 Port x 2(up to 40 Gbps), Support 15W (5V/3A) Power Delivering. Mini DisplayPort x 1
Compatible Drive	2 x 3.5" /2.5" SATA HDD/SSD (up to 6 Gbps)
Certification	CE/FCC
Storage Mode	2 x Independent (JBOD) / RAID 0 / RAID 1
Operating System Support	Windows 7 (64-bit), Windows 10 (64-bit), macOS 10.13 and later
Cooling System	1 x 4 cm Low noise fan
Electrical and Operating Requirements	<ul style="list-style-type: none"> * Line voltage: 100-240V AC * Frequency: 50Hz to 60Hz, single phase * Maximum continuous power: 96W * Operating temperature: 40° to 104° F (0° to 40° C) * Storage temperature: -4° to 116° F (-20° to 47° C) * Relative humidity: 5% to 95% noncondensing
Size and Weight	122(W)×63(H)×244(L) mm, 1.2 Kg
Product Code	EAN : 4713227440240 UPC : 884826504429
Carton	8 pcs per carton
Package Accessories	<ul style="list-style-type: none"> * GR3660-TB3 x 1 (with removable drive tray enclosed x 2) * Thunderbolt™ 3 Cable x 1 * AC Power Cable x 1 * User Manual x 1 * Screws & Keys

